



MOTORCYCLE SEATS

Mounting Suggestions: Sportster with 2.25, 3.25, 3.3, and 4.5 gallon tanks Tank Bibs

Mounting of Mustang Tank Bib:

Step 1 Remove seat from motorcycle.

Step 2 Remove gas cap from gas tank.

Step 3 Place tank bib on tank and align with hole for gas cap. Replace gas cap to keep bib stable during installation of tie straps or cords.

Note: Bibs are supplied with either leather tie straps or elastic cords, depending on bib style, gas tank size and model year.

Step 4 Pull tie straps (elastic cords) around both sides of and under bottom edges of tank. Elastic cords stay in place; leather ties should be threaded through loops at end of bib and tied in a knot.

Step 5 Attach lower end of bib to frame or gas tank mount using Velcro tabs.

Step 6 Replace seat.

Leather tie straps



Velcro tabs

Elastic cords



Enjoy the custom look of your new Mustang tank bib!



Velcro tabs

These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 860-582-9633, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Ref: part #'s 93113, 93114, 93115, 93116, 93187, 93188, 93189, 93190, 93322, 93323, 93326, 93327, 93328, 93329