



Installation Instructions for Mustang One-Piece Seat on 2009-2011 Kawasaki Vulcan 1700 Classic, 1700 Voyager, and 1700 Nomad

Removal of stock seats

1. Use ignition key to unlock rear seat. Pull seat up and forward to remove from the bike.



2. Remove the front seat from the bike.



3. Turn rear seat over and remove stock mounting bracket. It must be transferred to the Mustang seat.



4. Install stock mounting bracket onto bottom of Mustang seat using the supplied bolts.



Installation Instructions for Mustang One-Piece Seat on 2009-2011 Kawasaki Vulcan 1700 Classic, Voyager, and Nomad

Installation of Mustang one-piece seat

1. Note the two mounting points for the Mustang seat; front nose tab, and key-latch bracket.



2. Rear bracket stays on fender but is not used.



3. Engage tab on front of Mustang seat onto frame. Push center of seat down onto key-latch bracket until it clicks into place



These steps are guidelines to help you install your new Mustang product. If you need further assistance please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Ref. part #'s 76600, 76601, 76602, 76603, 76604, 76605, 76606, 76607, 76608, 76609, 79630, 79631, 79632, 79633, 79634, 79635, 79636, 79637