



Mounting Suggestions: Kawasaki Vaquero 2011-Up One-Piece Seat

Baseplate Features:

Baseplate is made of marine grade fiberglass and is a direct replacement of the stock seat.



Stock Seat Removal:

1. Insert ignition key into the lower left-hand side cover.
2. Turn key clockwise to unlock the seat pin bracket from the frame. Lift the rear portion of the seat up about 2", then slide it back and up off of the bike.
3. Remove the stock seat pin mounting bracket with a 10mm wrench and mount the stock seat bracket to the Mustang seat with the supplied 1/4-20 bolts. Tighten the bolts with a 7/16" wrench.



Mustang Seat Installation:

1. Align the seat nose bracket with the frame receiver. Slide the seat forward as far as it will go.
2. With the seat pin bracket aligned over the frame locking mechanism, push down on the center of the seat until an audible click is heard.
3. The seat is now locked and ready to ride.



Enjoy the comfort of your new Mustang seat!



These steps are guidelines to help you install your new Mustang Product. If you need further assistance, please call us at 800-243-1392 or 860-582-9633, Monday through Friday 9:00 – 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Ref part #76287, 76286, 79686, 79685, 79688, 79687